


OIL RESERVOIR with surge arrester

Material - STEEL Bottle - PLASTIC Finish - ZINC
Maximum operating temperature 65°C

Product Code	A	B	C	D	E	Capacity ml
		mm	mm	mm	mm	
OR 7708	1/4 BSP					
ORN 7708	1/4 NPT	62	12	45	38	35
OR 7714	1/4 BSP					
ORN 7714	1/4 NPT	74	13	54	44	63
OR 7724	1/4 BSP					
ORN 7724	1/4 NPT	86	13	63	57	127
OR 7730	1/4 BSP					
ORN 7730	1/4 NPT	93	13	69	64	170



OIL RESERVOIR

Material - BRASS Bottle - GLASS Finish - NICKEL
Seals - FIBRE & NITRILE 80 Maximum operating temperature: 80°C


Product Code	A	B	C	D	E	F	Capacity ml
		mm	mm	mm	mm	mm	
GRE 260	1/4 BSP	—					
GREN 260	1/4 NPT	—	99	14	60	60	140
GRE 360	3/8 BSP	1/8 BSP					
GREN 360	3/8 NPT	1/8 NPT					
GRE 268	1/4 BSP	—					
GREN 268	1/4 NPT	—	119	14	80	60	200
GRE 368	3/8 BSP	1/8 BSP					
GREN 368	3/8 NPT	1/8 NPT					
GRE 280	1/4 BSP	—					
GREN 280	1/4 NPT	—	148	14	100	80	400
GRE 380	3/8 BSP	1/8 BSP					
GREN 380	3/8 NPT	1/8 NPT					
*GRE 2100	1/4 BSP	—					
*GREN 2100	1/4 NPT	—					
*GRE 3100	3/8 BSP	1/8 BSP	189	14	120	100	900
*GREN 3100	3/8 NPT	1/8 NPT					
*GRE 4100	1/2 BSP	1/4 BSP					
*GREN 4100	1/2 NPT	1/4 NPT					
*GRE 2133	1/4 BSP	—					
*GREN 2133	1/4 NPT	—					
*GRE 3133	3/8 BSP	1/8 BSP	225	14	150	133	1900
*GREN 3133	3/8 NPT	1/8 NPT					
*GRE 4133	1/2 BSP	1/4 BSP					
*GREN 4133	1/2 NPT	1/4 NPT					
*GRE 2150	1/4 BSP	—					
*GREN 2150	1/4 NPT	—					
*GRE 3150	3/8 BSP	1/8 BSP	260	14	180	150	3000
*GREN 3150	3/8 NPT	1/8 NPT					
*GRE 4150	1/2 BSP	1/4 BSP					
*GREN 4150	1/2 NPT	1/4 NPT					

* Available with low level switch. If required, add suffix "FS" to product code.

Material - BRASS Bottle - PLEXIGLASS Finish - NICKEL

Seals - FIBRE & NITRILE 80 Maximum operating temperature: 70°C

Product Code	A	B	C	D	E	F	Capacity ml
		mm	mm	mm	mm	mm	
PRE 260	1/4 BSP	—					
PREN 260	1/4 NPT	—	99	14	60	60	140
PRE 360	3/8 BSP	1/8 BSP					
PREN 360	3/8 NPT	1/8 NPT					
PRE 268	1/4 BSP	—					
PREN 268	1/4 NPT	—	119	14	80	60	200
PRE 368	3/8 BSP	1/8 BSP					
PREN 368	3/8 NPT	1/8 NPT					



OIL RESERVOIR/ continued

Material - BRASS Bottle - PLEXIGLASS Finish - NICKEL

Product Code	A	B	C mm	D mm	E mm	F mm	Capacity ml
PRE 280	1/4 BSP	—					
PREN 280	1/4 NPT	—	148	14	100	80	400
PRE 380	3/8 BSP	1/8 BSP					
PREN 380	3/8 NPT	1/8 NPT					
*PRE 2100	1/4 BSP	—					
*PREN 2100	1/4 NPT	—					
*PRE 3100	3/8 BSP	1/8 BSP	189	14	120	100	900
*PREN 3100	3/8 NPT	1/8 NPT					
*PRE 4100	1/2 BSP	1/4 BSP					
*PREN 4100	1/2 NPT	1/4 NPT					
*PRE 2133	1/4 BSP	—					
*PREN 2133	1/4 NPT	—					
*PRE 3133	3/8 BSP	1/8 BSP	225	14	150	133	1,900
*PREN 3133	3/8 NPT	1/8 NPT					
*PRE 4133	1/2 BSP	1/4 BSP					
*PREN 4133	1/2 NPT	1/4 NPT					
*PRE 2150	1/4 BSP	—					
*PREN 2150	1/4 NPT	—					
*PRE 3150	3/8 BSP	1/8 BSP	260	14	180	150	3000
*PREN 3150	3/8 NPT	1/8 NPT					
*PRE 4150	1/2 BSP	1/4 BSP					
*PREN 4150	1/2 NPT	1/4 NPT					

* Available with low level switch. If required add suffix "FS" to product code.

OIL RESERVOIRS - MANUAL ON/OFF

Material - BRASS Bottle - GLASS Finish - NICKEL

Seals - FIBRE & NITRILE 80 Maximum operating temperature: 80°C

Product Code	A	B mm	C mm	D mm	E mm	Capacity ml
GOS 260	1/4 BSP					
GOSN 260	1/4 NPT	150	14	60	60	140
GOS 268	1/4 BSP					
GOSN 268	1/4 NPT	170	14	80	60	200
GOS 280	1/4 BSP					
GOSN 280	1/4 NPT	210	14	100	80	400
*GOS 2100	1/4 BSP					
*GOSN 2100	1/4 NPT	250	14	120	100	900
*GOS 2133	1/4 BSP					
*GOSN 2133	1/4 NPT	295	14	150	133	1,900
*GOS 2150	1/4 BSP					
*GOSN 2150	1/4 NPT	325	14	180	150	3000

* Available with low level switch. If required add suffix "FS" to product code.

Material - BRASS Bottle - PLEXIGLASS Finish - NICKEL

Seals - FIBRE & NITRILE 80 Maximum operating temperature: 70°C

Product Code	A	B mm	C mm	D mm	E mm	Capacity ml
POS 260	1/4 BSP					
POSN 260	1/4 NPT	150	14	60	60	140
POS 268	1/4 BSP					
POSN 268	1/4 NPT	170	14	80	60	200
POS 280	1/4 BSP					
POSN 280	1/4 NPT	210	14	100	80	400
*POS 2100	1/4 BSP					
*POSN 2100	1/4 NPT	250	14	120	100	900
*POS 2133	1/4 BSP					
*POSN 2133	1/4 NPT	295	14	150	133	1,900
*POS 2150	1/4 BSP					
*POSN 2150	1/4 NPT	325	14	180	150	3000

* Available with low level switch. If required add suffix "FS" to product code.

