

SPRING GREASERS - STEEL RESERVOIR

| | | |
|---|------------|-------|
| | Dimensions | |
| A | = | 48mm |
| B | = | 135mm |
| C | = | 185mm |

| | | |
|----------|---|-------------|
| Capacity | = | 80cc |
| Material | = | Steel Body |
| | = | Fibre Seals |
| Finish | = | Zinc Plated |

Operating temperature - 25°C to + 100°C

Suitable for use with greases which do not separate under pressure



STANDARD SPRING PRESSURE (RED CAP)

Mounted directly to lubrication point.
Suitable for use with light grease

| Product Code | Thread | Capacity | Spring Pressure |
|--------------|----------|----------|-----------------|
| SGS 280 | 1/4" BSP | 80cc | 4.5 Newtons |
| SGSN 280 | 1/4" NPT | | |

MEDIUM SPRING PRESSURE (BLACK CAP)

Mounted directly to lubrication point.
or up to 30mm of large bore pipe.

| Product Code | Thread | Capacity | Spring Pressure |
|--------------|----------|----------|-----------------|
| SGS 280/M | 1/4" BSP | 80cc | 6 Newtons |
| SGSN 280/M | 1/4" NPT | | |

STRONG SPRING PRESSURE (YELLOW CAP)

Suitable for use with large bore pipe up to 50mm

| Product Code | Thread | Capacity | Spring Pressure |
|--------------|----------|----------|-----------------|
| SGS 280/S | 1/4" BSP | 80cc | 7 Newtons |
| SGSN 280/S | 1/4" NPT | | |

FEATURES

- Re-fillable via grease nipple.
- Can be mounted in any position.
- Level indicator rod.
- No maintenance required.
- Constant lubrication pressure

